

ω

INFERMACIÓN TECNIO

t e c h n i c a l INFORMATION EBN

DECLARATION OF PERFORMANCE

CIFRE GROUP ™

JANUARY 2019





Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

Dear customers,

As you know, as of 1st of July 2013, the new European Regulation for Construction Products, Nr. 305/2011, comes into force, and in order for us to adapt to it, we send you the DECLARATIONS OF PERFORMANCE, valid for the different product families.

For your information, declarations have been divided into groups:

Nr. 001-CPR-PRBR-2013-07-01. GLOSS PORCELAIN Nr. 002-CPR-G-2013-07-01. STONEWARE NR. 003-CPR-A-2013-07-01. WALL TILES Nr. 004-CPR-PR-2013-07-01. MATT PORCELAIN Nr. 005-CPR-GAD-2013-07-01. ANTISLIP STONEWARE Nr. 006-CPR-PRAD-2013-07-01. ANTISLIP PORCELAIN Nr. 007-CPR-PE-2013-07-01. SPECIAL PIECES N° 008-CPR-GPAD-2013-07-01. ANTISLIP PORCELAIN STONEWARE N° 009-CPR-PRF-2013-07-01. THIN THICKNESS N° 010-CPR-EXT-2013-11-06. PORCELAIN EXTRUDED

The said documents are available in our website, www.cifreceramica.com, in section downloads/declaration of features. (Home / Cifre Ceramica / Downloads) In case you need a paper copy, ask your sales representative at Cifre Cerámica and you will be served in the shortest delay.

DECLARATION OF PERFORMANCE

Nº 001-CPR-PRBR-2013-07-01

Onda, 1st July 2013

CITIC cerámica

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%<E<3%, type 1

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1-A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1100 N	EN 14411
Bond Strength/Adhesion for (N/mm²)	> 1 Nw/mm² with cementi- tious adhesive type C	
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Nebot Manager Director Cifre Ceramica S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.



Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 002-CPR-G-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 3%<E≤6%, type 2

2.- Intended use.

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	NDP	EN 14411
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS NDP	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Neoot Manager Director Cifre Ceramice,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

SGS ES07/3348

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 003-CPR-A-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption E > 10%, type 3

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Bond Strength/Adhesion for (N/mm²)	> 1 Nw/mm² with cementi- tious adhesive type C	EN 14411
Thermal shock resistance	NDP	
Durability: · Indoor use. · Outdoor Use	PASS NDP	



The performance of the product identified in point 1 is in conformity with the declared performance in point 6.



Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 004-CPR-PR-2013-07-01

Onda, 1st July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%≥E, type 4

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1300 N	
Bond Strength/Adhesion for (N/mm²)	> 1 Nw/mm² with cementi- tious adhesive type C	EN 14411
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Neoot Manager Director Cifre Ceramice,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

SGS ESO7/3348

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



DECLARATION OF PERFORMANCE

№ 005-CPR-GAD-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 3%<E≤6%, type 5

2.- Intended use.

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	EN 14411
Thermal shock resistance	NDP	
Durability: • Indoor use. • Outdoor Use	PASS NDP	
Tactility :	NDP	



The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

ESOT/3348





CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 006-CPR-PRAD-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%≥E, type 6

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1300 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	EN 14411
Bond Strength/Adhesion for (N/mm ²)	>1 Nw/mm ² with cementi- tious adhesive type C	
Thermal shock resistance	PASS	
Durability: · Indoor use. · Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacture Enrique Cifre Manager Dire Cifre Ceramic

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

ESOT/3348

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com



DECLARATION OF PERFORMANCE

№ 007-CPR-PE-2013-07-01 Onda, 1ST July 2013 **1.- Unique identification code of de product type.**

Special pieces of dry-pressed ceramic tiles, type 7

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Bond Strength/Adhesion for (N/mm²)	NDP	
Thermal shock resistance	NDP	EN 14411
Durability: • Indoor use. • Outdoor Use	PASS NDP	



The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

SCS ES07/3348





CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 008-CPR-GPAD-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%<E<3%, type 8

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1100 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	EN 14411
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Neoot Manager Director Cifre Ceramice,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

SGS ES07/3348





CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 009-CPR-PRF-2013-07-01

Onda, 11 Sept 2017

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles and thickness <7.5mm with water absorption 0.5%≥E, type 9

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 700 N	EN 14411
Bond Strength/Adhesion for (N/mm²)	> 1 Nw/mm² with cementi- tious adhesive type C	
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Neoot Manager Director Cifre Ceramice,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

ESO7/3348





CIFRE GROUP ™

DECLARATION OF PERFORMANCE

Nº 010-CPR-EXT-2013-11-06

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Extruded tiles, with water absorption 0.5%<E**s**3%, type 10

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1100 N	EN 14411
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	
Thermal shock resistance	PASS	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

Signed for and on behalf of the manufacturer by Enrique Cifre Neoot Manager Director Cifre Ceramice,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.



Ctra. Vila-real - Onda, km 10 12200 Onda - Castellón SPAIN www.cifreceramica.com e-mail: cifre@cifreceramica.com Tel.: +34 964 506 969 Fax: + 34 964 521 593

