

INFORMACIÓN TECNICA

T E C H N I C A L INFORMATION

EN



DECLARATION OF PERFORMANCE BS

CIFRE GROUP ™ MARCH 2021





Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com

Dear customers:

As you know, the new British Regulation for Construction Products, comes into force, and in order for us to adapt to it, we send you the DECLARATIONS OF PERFORMANCE BS, valid for the different product families.

For your information, declarations have been divided into groups:

Nr. 001-CPR-PRBR-2021-03-01. GLOSS PORCELAIN

Nr. 002-CPR-G-2021-03-01. STONEWARE

NR. 003-CPR-A-2021-03-01. WALL TILES

Nr. 004-CPR-PR-2021-03-01. MATT PORCELAIN

Nr. 005-CPR-GAD-2021-03-01. ANTISLIP STONEWARE

Nr. 006-CPR-PRAD-2021-03-01. ANTISLIP PORCELAIN

Nr. 007-CPR-PE-2021-03-01. SPECIAL PIECES

Nº 008-CPR-GPAD-2021-03-01. ANTISLIP PORCELAIN STONEWARE

№ 009-CPR-PRF-2021-03-01. THIN THICKNESS

Nº 010-CPR-EXT-2021-03-01. PORCELAIN EXTRUDED

The said documents are available in our website, www.cifreceramica.com, in section downloads/declaration of features.

(Home / Cifre Ceramica / Downloads)

In case you need a paper copy, ask your sales representative at Cifre Cerámica and you will be served in the shortest delay.





GLOSSY PORCELAIN TILES

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 001-CPR-PRBR-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%<E≤3%, type 1

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS-EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1-A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 1100 N	
Bond Strength/Adhesion for (N/mm2)	> 1 Nw/mm2 with cementitious adhesive type C	BS - EN 14411
Thermal shock resistance	PASS	
Durability:		
· Indoor use.	PASS	
· Outdoor Use	PASS	
Tactility:	NDP	

Signed for and on behalf of the manufacturer by

Manager Director
Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 002-CPR-G-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 3%<E≤6%, type 2

2.- Intended use.

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	NDP	BS - EN 14411
Thermal shock resistance	PASS	
Durability: Indoor use. Outdoor Use Tactility:	PASS NDP NDP	_

Signed for and on behalf of the /manufacturer by

> Enrique Cifre Nebot Manager Director Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





TYPE3

WALL TILES

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 003-CPR-A-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption E > 10%, type 3

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1	
Release of dangerous substance, for:	NDP	
Bond Strength/Adhesion for (N/mm2)	> 1 Nw/mm2 with cementitious adhesive type C	BS - EN 14411
Thermal shock resistance	NDP	
Durability: Indoor use. Outdoor Use	PASS NDP	

Signed for and on behalf of the manufacturer by

Manager Director
Cifre Ceramica,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.







Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 004-CPR-PR-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%≥E, type 4

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 1300 N	
Bond Strength/Adhesion for (N/mm2)	> 1 Nw/mm2 with cemen- titious adhesive type C	BS - EN 14411
Thermal shock resistance	PASS	
Durability: Indoor use. Outdoor Use	PASS PASS	
Tactility:	NDP	

Signed for and on behalf of the /manufacturer by

> Enrique Cifre Nebot Manager Director Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





TYPE 5

ANTISLIP STONEWARE

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 005-CPR-GAD-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 3%<E≤6%, type 5

2.- Intended use.

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	BS - EN 14411
Thermal shock resistance	NDP	
Durability: Indoor use. Outdoor Use Tactility:	PASS NDP NDP	

Signed for and on behalf of the

Manager Director
Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.







Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 006-CPR-PRAD-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%≥E, type 6

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for:	NDP	
Breaking strength	≥ 1300 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	BS - EN 14411
Bond Strength/Adhesion for (N/mm²)	> 1 Nw/mm² with cemen- titious adhesive type C	
Thermal shock resistance	PASS	
Durability:		
· Indoor use.	PASS	
· Outdoor Use	PASS	
Tactility:	NDP	

Signed for and on behalf of the

Manager Director
Cifre Ceramica,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





TYPE 7

SPECIAL PIECES

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 007-CPR-PE-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Special pieces of dry-pressed ceramic tiles, type 7

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1	
Release of dangerous substance, for:	NDP	
Bond Strength/Adhesion for (N/mm2)	NDP	
Thermal shock resistance	NDP	BS - EN 14411
Durability:		
· Indoor use.	PASS	
Outdoor Use	NDP	
	I	I I

Signed for and on behalf of the /manufacturer by

> Enrique Cifre Nebot Manager Director Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





HARMONISED





Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 008-CPR-GPAD-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption 0.5%<E≤3%, type 8

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 1100 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	BS - EN 14411
Thermal shock resistance	PASS	
Durability: Indoor use. Outdoor Use	PASS PASS	
Tactility:	NDP	

Signed for and on behalf of the manufacturer by

Manager Director
Cifre Ceramica,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





TYPE 9

THIN THICKNESS

Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 009-CPR-PRF-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles and thickness <7.5mm with water absorption 0.5%≥E, type 9

2.- Intended use.

For indoor and outdoor walls and floorings

CIFNEODER AND CANBALT address of the manufacturer.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for: Cadmium Lead Others	NDP	
Breaking strength	≥ 700 N	
Bond Strength/Adhesion for (N/mm2)	> 1 Nw/mm2 with cementitious adhesive type C	BS - EN 14411
Thermal shock resistance	PASS	
Durability: Indoor use. Outdoor Use	PASS PASS	
Tactility:	NDP	

Signed for and on behalf of the manufacturer by

Manager Director
Cifre Ceramica, S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





Ctra. Vila-real - Onda, Km. 10 12200 Onda, Castellón Apdo. Correos, Nº 350, 12540 Vila-real, Castellón. Tel./Phone: +34 964 506 969 Fax: +34 964 521 593 e-mail: cifre@cifreceramica.com www.cifreceramica.com

DECLARATION OF PERFORMANCE

Nº 010-CPR-EXT-2021-03-01

Onda, 1ST March 2021

1.- Unique identification code of de product type.

Extruded tiles, with water absorption 0.5%<E≤3%, type 10

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA

(Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

BS - EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	
Release of dangerous substance, for:	NDP	
Breaking strength	≥ 1100 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	BS - EN 14411
Thermal shock resistance	PASS	
Durability: Indoor use. Outdoor Use	PASS PASS	
Tactility:	NDP	

Signed for and on behalf of the manufacturer by

Manager Director
Cifre Ceramica,S.L.

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.





Tel.: +34 964 506 969

Fax: + 34 964 521 593