

cifrecerámica

T E C H N I C A L
INFORMATION



DECLARATIONS OF PERFORMANCE

Dear customers:

As you know, as of 1st of July 2013, the new European Regulation for Construction Products, Nr. 305/2011, comes into force, and in order for us to adapt to it, we send you the DECLARATIONS OF PERFORMANCE, valid for the different product families.

For your information, declarations have been divided into groups:

Nr. 001-CPR-PRBR-2013-07-01. GLOSS PORCELAIN

Nr. 002-CPR-G-2013-07-01. STONEWARE

NR. 003-CPR-A-2013-07-01. WALL TILES

Nr. 004-CPR-PR-2013-07-01. MATT PORCELAIN

Nr. 005-CPR-GAD-2013-07-01. ANTISLIP STONEWARE

Nr. 006-CPR-PRAD-2013-07-01. ANTISLIP PORCELAIN

Nr. 007-CPR-PE-2013-07-01. SPECIAL PIECES

N° 008-CPR-GPAD-2013-07-01. ANTISLIP PORCELAIN STONEWARE

N° 009-CPR-PRF-2013-07-01. THIN THICKNESS

N° 010-CPR-EXT-2013-11-06. PORCELAIN EXTRUDED

The said documents are available in our website,

www.cifreceramica.com, in section downloads/declaration of features.

(Home / Cifre Ceramica / Downloads)

In case you need a paper copy, ask your sales representative at Cifre Cerámica and you will be served in the shortest delay.



GLOSSY PORCELAIN TILES

TYPE 1

DECLARATION OF PERFORMANCE

N° 001-CPR-PRBR-2013-07-01

Onda, 1ST July 2013

1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption $0.5\% < E \leq 3\%$, type 1

2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1-A1 _{FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1100 N	
Bond Strength/Adhesion for (N/mm ²)	> 1 Nw/mm ² with cementitious adhesive type C2	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

**STONEWARE****TYPE 2****DECLARATION OF PERFORMANCE**

N° 002-CPR-G-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption $3\% < E \leq 6\%$, type 2**2.- Intended use.**

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 _{FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	NDP	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS NDP	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

**WALL TILES****TYPE 3****DECLARATION OF PERFORMANCE**

N° 003-CPR-A-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**

Dry-pressed ceramic tiles, with water absorption E > 10%, type 3

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Bond Strength/Adhesion for (N/mm ²)	> 1 Nw/mm ² with cementitious adhesive type C2	
Thermal shock resistance	NDP	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Cerámica S.L.

**MATT PORCELAIN****TYPE 4****DECLARATION OF PERFORMANCE**

N° 004-CPR-PR-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption $0.5\% \geq E$, type 4**2.- Intended use.**

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1-A1 _{FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1300 N	
Bond Strength/Adhesion for (N/mm ²)	> 1 Nw/mm ² with cementitious adhesive type C2	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

**ANTISLIP STONWARE****TYPE 5****DECLARATION OF PERFORMANCE**

N° 005-CPR-GAD-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption $3\% < E \leq 6\%$, type 5**2.- Intended use.**

For indoor floorings.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A _{1FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1000 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	
Thermal shock resistance	NDP	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS NDP	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Cerámica S.L.

**ANTISLIP PORCELAIN****TYPE 6****DECLARATION OF PERFORMANCE**

N° 006-CPR-PRAD-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption $0.5\% \geq E$, type 6**2.- Intended use.**

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A _{1FL}	EN 14411
Release of dangerous substance, for: • Cadmium • Lead • Others	NDP	
Breaking strength	≥ 1300 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	
Bond Strength/Adhesion for (N/mm ²)	> > 1 Nw/mm ² with cementitious adhesive type C2	
Thermal shock resistance	NDP	
Durability: • Indoor use. • Outdoor Use	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

**SPECIAL PIECES****TYPE 7****DECLARATION OF PERFORMANCE**

N° 007-CPR-PE-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**

Special pieces of dry-pressed ceramic tiles, type 7

2.- Intended use.

For indoor walls.

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Bond Strength/Adhesion for (N/mm ²)	NDP	
Thermal shock resistance	NDP	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Cerámica S.L.

**ANTISLIP STONEWARE PORCELAIN****TYPE 8****DECLARATION OF PERFORMANCE**

N° 008-CPR-GPAD-2013-07-01

Onda, 1ST July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption $0.5\% < E \leq 3\%$, type 8**2.- Intended use.**

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A _{1FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1100 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

**THIN THICKNESS****TYPE 9****DECLARATION OF PERFORMANCE**

N° 009-CPR-PRF-2013-07-01

Onda, 11 Sept 2017

1.- Unique identification code of de product type.Dry-pressed ceramic tiles and thickness <7.5mm with water absorption $0.5\% \geq E$, type 9**2.- Intended use.**

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 700 N	
Bond Strength/Adhesion for (N/mm ²)	> 1 Nw/mm ² with cementitious adhesive type C2	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Cerámica S.L.


PORCELAIN EXTRUDED
TYPE 10
DECLARATION OF PERFORMANCE

N° 010-CPR-EXT-2013-11-06

Onda, 1ST July 2013
1.- Unique identification code of de product type.
Extruded tiles, with water absorption $0.5\% < E \leq 3\%$, type 10
2.- Intended use.

For indoor and outdoor walls and floorings

3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

4.- System of assessment and verification of constancy of performance.

4

5.- Harmonised standard

EN 14411:2016

6.- Declared performance.

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 - A1 _{FL}	EN 14411
Release of dangerous substance, for: <ul style="list-style-type: none"> • Cadmium • Lead • Others 	NDP	
Breaking strength	≥ 1100 N	
Slipperiness, as: PTV SLIDER 57 CEN/TS 16165	Rd > 45	
Thermal shock resistance	PASS	
Durability: <ul style="list-style-type: none"> • Indoor use. • Outdoor Use 	PASS PASS	
Tactility :	NDP	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf
of the manufacturer by

Enrique Cifre Nebot
CEO Cifre Ceramica S.L.

cifrecerámica